

# LANDINI MYTHOS MYTHOS 105 (TOP/TOP TRONIC) (1999-2005)



**ENGINE** Perkins 1104C-44T  
Capacity: 8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Agridiesel CRD+ 15W-40**

PRODUCT RECOMMENDATION 2

**Multifleet SHPD 15W-40**

*Change every 250 hours/ 12 months*

## DIFFERENTIAL FRONT

Capacity: 5,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Agrifluid Synth XHP Ultra**

PRODUCT RECOMMENDATION 2

**Kroontrak MTH 10W-30**

PRODUCT RECOMMENDATION 3

**Agrifluid HT**

*Change every 1000 hours/ 12 months*

## HUB REDUCTIONS FRONT

Capacity: 1,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90**

*Change every 1000 hours/ 12 months*

## HUB REDUCTIONS REAR

Capacity: 4,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90**

*Change every 1000 hours/ 12 months*

## TRANSAXLE/HYDRAULIC SYSTEM Power-Five

Capacity: 59 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Agrifluid Synth XHP Ultra**

PRODUCT RECOMMENDATION 2

**Kroontrak MTH 10W-30**

PRODUCT RECOMMENDATION 3

**Agrifluid HT**

*Change every 1000 hours/ 12 months*

# LANDINI MYTHOS MYTHOS 105 (TOP/TOP TRONIC) (1999-2005)



## TRANSAXLE/HYDRAULIC SYSTEM Top-Tronic

Capacity: 65 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Agrifluid HT-Plus***Change every 1000 hours/ 12 months*

## HYDRAULIC BRAKE SYSTEM

Capacity: 1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**LHM +**

## HYDRAULIC CLUTCH SYSTEM

Capacity: 1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**LHM +**

## GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Labora Grease**

PRODUCT RECOMMENDATION 2

**Q5 MP Calcep Grease EP 2**

PRODUCT RECOMMENDATION 3

**MP Lithep Grease EP 2***Check every 100 hours*

## COOLING SYSTEM

Capacity: 22 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Coolant -38 Organic NF**

PRODUCT RECOMMENDATION 2

**Coolant -26***Change every 1000 hours/ 12 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.