

| ENGINE Perkins 1104C-44<br>Capacity: 8 liter |                          |          |
|--|--------------------------|----------|
| USE  |                          | CLIMATE  |
| Normal                                       |                          | Moderate |
| PRODUCT RECOMMENDATION 1                     | PRODUCT RECOMMENDATION 2 |          |
| Agridiesel CRD+ 15W-40                       | Multifleet SHPD 15W-40   |          |
|  |                          |          |

Check every 10 hours, change every 250 hours

| DIFFERENTIAL FRONT<br>Capacity: 5,8 liter |                           |                          |
|---|---------------------------|--------------------------|
| USE                                       |                           | CLIMATE                  |
| Normal                                    |                           | Moderate                 |
| PRODUCT RECOMMENDATION 1                  | PRODUCT RECOMMENDATION 2  | PRODUCT RECOMMENDATION 3 |
| Kroontrak CVT 10W-40                      | Agrifluid Synth XHP Ultra | Agrifluid HT-Plus        |

Check every 100 hours, change every 1000 hours/ 12 months

| HUB REDUCTIONS FRONT<br>Capacity: 1,5 liter |                             |          |
|---|-----------------------------|----------|
| USE   |                             | CLIMATE  |
| Normal                                      |                             | Moderate |
| PRODUCT RECOMMENDATION 1                    | PRODUCT RECOMMENDATION 2    |          |
| Gearlube GL-5 80W-90                        | Unigear HS GL-3/GL-5 80W-90 |          |

Check every 100 hours, change every 1000 hours/ 12 months

| HUB REDUCTIONS REAR<br>Capacity: 3,5 liter |                             |          |
|--|-----------------------------|----------|
| USE  |                             | CLIMATE  |
| Normal                                     |                             | Moderate |
| PRODUCT RECOMMENDATION 1                   | PRODUCT RECOMMENDATION 2    |          |
| Gearlube GL-5 80W-90                       | Unigear HS GL-3/GL-5 80W-90 |          |
|  |                             |          |

Check every 100 hours, change every 1000 hours/ 12 months

## LANDINI VISION VISION 85 (2004-2010)



| TRANSAXLE/HYDRAULIC SYSTEM Pow<br>Capacity: 50 liter | verShuttle         |          |
|--|--------------------|----------|
| USE  |                    | CLIMATE  |
| Normal   |                    | Moderate |
| PRODUCT RECOMMENDATION 1                             |                    |          |
| Agrifluid HT-Plus                                    |                    |          |
| Check every 100 hours, change every 100              | 0 hours/ 12 months |          |
| USE  |                    | CLIMATE  |
| Initial service                                      |                    | Moderate |
| PRODUCT RECOMMENDATION 1                             |                    |          |
| Agrifluid HT-Plus                                    |                    |          |
| Change every 500 hours                               |                    |          |

 TRANSAXLE/HYDRAULIC SYSTEM Speed-Five Capacity: 38 liter

 CLIMATE

 USE

 Normal
 CLIMATE

 PRODUCT RECOMMENDATION 1
 PRODUCT RECOMMENDATION 2
 PRODUCT RECOMMENDATION 3

 Kroontrak CVT 10W-40
 Agrifluid Synth XHP Ultra
 Agrifluid HT-Plus

 Check every 100 hours, change every 100-hours/ 12 months
 CLIMATE

| Initial service          |                           | Moderate                 |
|--------------------------|---------------------------|--------------------------|
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2  | PRODUCT RECOMMENDATION 3 |
| Kroontrak CVT 10W-40     | Agrifluid Synth XHP Ultra | Agrifluid HT-Plus        |

Change every 500 hours

| HYDRAULIC BRAKE SYSTEM<br>Capacity: 1 liter |          |
|---|----------|
| USE   | CLIMATE  |
| Normal                                      | Moderate |
| PRODUCT RECOMMENDATION 1                    |          |
| LHM +                                       |          |
| Charle avery EQ hours                       |          |

Check every 50 hours

## LANDINI VISION VISION 85 (2004-2010)



| GREASE POINTS/NIPPLES    |                          |                          |
|--------------------------|--------------------------|--------------------------|
| USE                      |                          | CLIMATE                  |
| Normal                   |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease            | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2    |

Change every 50 hours

| COOLING SYSTEM<br>Capacity: 22 liter                     |                          |          |  |
|--|--------------------------|----------|--|
| USE  |                          | CLIMATE  |  |
| Normal   |                          | Moderate |  |
| PRODUCT RECOMMENDATION 1                                 | PRODUCT RECOMMENDATION 2 |          |  |
| Coolant -38 Organic NF                                   | Coolant -26              |          |  |
| Chack avery 10 hours, change avery 1000 hours/ 12 months |                          |          |  |

Check every 10 hours, change every 1000 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.