

# LAVERDA L SERIES L 624H (1991 AND AFTER)

**ENGINE**

Capacity: 18 liter, Filter capacity: 2 liter

**USE**

Normal

**CLIMATE**

Mediterranean

**PRODUCT RECOMMENDATION 1****Multifleet SHPD 15W-40****PRODUCT RECOMMENDATION 2****Multifleet SCD 40****PRODUCT RECOMMENDATION 3****Multifleet SCD 30***Check every 10 hours, change every 450 hours***USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Kroontrak MTH 10W-30****PRODUCT RECOMMENDATION 2****Multifleet SHPD 10W-40***Check every 10 hours, change every 450 hours***USE**

Normal

**CLIMATE**

Cold

**PRODUCT RECOMMENDATION 1****Multifleet SCD 20W-20***Check every 10 hours, change every 450 hours***USE**

Normal

**CLIMATE**

Arctic

**PRODUCT RECOMMENDATION 1****Multifleet SCD 10W***Check every 10 hours, change every 450 hours***HUB REDUCTIONS FRONT**

Capacity: 5,5 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Gearlube GL-5 80W-90****PRODUCT RECOMMENDATION 2****Unigear HS GL-3/GL-5 80W-90***Change every 450 hours***TRANSAXLE MANUAL**

Capacity: 12 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Gearlube GL-5 80W-90****PRODUCT RECOMMENDATION 2****Unigear HS GL-3/GL-5 80W-90***Check every 10 hours, change every 450 hours*

# LAVERDA L SERIES L 624H (1991 AND AFTER)



## HYDRAULIC SYSTEM

Capacity: 17 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Perlus H 46</b>	<b>Perlus AF 46</b>	

Check every 10 hours, change every 450 hours

## HYDRAULIC SYSTEM HYDROSTATIC DRIVE

Capacity: 46 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Perlus H 46</b>	<b>Perlus AF 46</b>	

Check every 10 hours, change every 450 hours

## HYDRAULIC BRAKE SYSTEM

Capacity: 0,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Drauliquid DOT 3</b>		

Check every 75 hours, change every 12 months

## GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcepe Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

Check every 75 hours

## COOLING SYSTEM

Capacity: 45 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

Check every 75 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the

PRODUCT RECOMMENDATION

# LAVERDA L SERIES L 624H (1991 AND AFTER)



*information contained herein is subject to changes without notification.*