

# LINDNER GEOTRAC 3 GEOTRAC 73 (2004 AND AFTER)



**ENGINE** Perkins 1103C-33T  
Capacity: 6,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Agrisynth LSP 10W-40**

PRODUCT RECOMMENDATION 2

**Kroontrak CVT 10W-40**

PRODUCT RECOMMENDATION 3

**Agrisynth MSP 10W-40**

*Check every 10 hours, change every 250 hours/ 12 months*

## DIFFERENTIAL FRONT

Capacity: 7,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90**

*Check every 250 hours, change every 1000 hours*

## HUB REDUCTIONS FRONT

Capacity: 0,7 liter (each hub)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90**

*Change every 250 hours/ 12 months*

## POWER TAKE OFF FRONT

Capacity: 2,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Agrifluid HT-Plus**

PRODUCT RECOMMENDATION 2

**Kroontrak MTH 10W-30**

PRODUCT RECOMMENDATION 3

**Agrifluid HT**

*Check every 250 hours, change every 500 hours*

## TRANSMISSION

Capacity: 34 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Agrifluid HT-Plus**

PRODUCT RECOMMENDATION 2

**Kroontrak MTH 10W-30**

PRODUCT RECOMMENDATION 3

**Agrifluid HT**

*Check every 250 hours, change every 1000 hours*

# LINDNER GEOTRAC 3 GEOTRAC 73 (2004 AND AFTER)



## HYDRAULIC SYSTEM POWER STEERING

Capacity: 16 liter, Capacity: 17 liter (Hydraulic tank)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Perlus H 46</b>	<b>Perlus AF 46</b>	

*Check every 250 hours, change every 1000 hours*

## HYDRAULIC BRAKE/CLUTCH SYSTEM

Capacity: 1,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	

*Change every 24 months*

## GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>

*Change every 50 hours*

## COOLING SYSTEM

Capacity: 17 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant SP 12</b>	<b>Coolant SP 12 EVO</b>	

*Change every 72 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.