

LINDNER N, A 1700 N, A (1990-1994)

ENGINE Perkins
Capacity: 8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Kroontrak MTH 10W-30

Check every 10 hours, change every 250 hours/ 12 months

DIFFERENTIAL FRONT

Capacity: 7,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90

Check every 500 hours, change every 1000 hours

HUB REDUCTIONS FRONT

Capacity: 0,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90

Check every 50 hours, change every 250 hours

HUB REDUCTIONS REAR

Capacity: 2,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agrifluid HT-Plus

PRODUCT RECOMMENDATION 2

SP Gear 5015

PRODUCT RECOMMENDATION 3

Gearlube GL-4 80W

Check every 500 hours, change every 1000 hours

TRANSAXLE MANUAL 16/8

Capacity: 24,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agrifluid HT-Plus

PRODUCT RECOMMENDATION 2

SP Gear 5015

PRODUCT RECOMMENDATION 3

Gearlube GL-4 80W

Check every 500 hours, change every 1000 hours

LINDNER N, A 1700 N, A (1990-1994)**HYDRAULIC SYSTEM POWER STEERING**

Capacity: 16 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	Perlus AF 46	

*Check every 250 hours, change every 500 hours***COOLING SYSTEM**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.