## MANITOU MANISCOPIC MT/MTA MRT 1850 (1998 AND AFTER)



<b>ENGINE</b> Perkins 1004.4 Capacity: 7,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SHPD 15W-40		
Check every 300 hours, change every 90	O hours	
CREEP SPEED GEARBOX Capacity: 3,6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Change every 300 hours		
DIFFERENTIAL		
Capacity: 11 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Change every 900 hours		
HUB REDUCTIONS FRONT Capacity: 1,6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Change every 900 hours		
HUB REDUCTIONS REAR		
Capacity: 1,6 liter		
USE		CLIMATE

Normal

**Agrifluid HT** 

PRODUCT RECOMMENDATION 1

Change every 900 hours

Moderate

## MANITOU MANISCOPIC MT/MTA MRT 1850 (1998 AND AFTER)



TRANSFERBOX Capacity: 2,8 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT	
Change every 900 hours	

TRANSMISSION/HYDRAULIC SYS	STEM	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Perlus H 46	Perlus AF 46	
Change every 900 hours		

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

GREASE POINTS/NIPPLES TELESCOPIC BOOM		
USE		CLIMATE
Normal	1	Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

COOLING SYSTEM Capacity: 25 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Change every 900 hours	'	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.