MARSHALL ALL MODELS 302 (1982-1985)



ENGINE Leyland 1.8 TD Capacity: 5,8 liter			
USE		CLIMATE	
Normal		Tropical	
PRODUCT RECOMMENDATION 1			
HDX 30			
Check every 10 hours, change every 400	hours		
USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
HDX 20W-20	HDX 10W		

Check every 10 hours, change every 400 hours

HUB REDUCTIONS REAR Capacity: 1,3 liter	
USE	CLIMATE
Normal	Tropical
PRODUCT RECOMMENDATION 1	
HDX 30	

Check every 800 hours, change every 400 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
HDX 20W-20	HDX 10W	
Check every 800 hours, change every 400	hours	

 TRANSAXLE MANUAL 9/3

 Capacity: 10,8 liter

 USE
 CLIMATE

 Normal
 Tropical

 PRODUCT RECOMMENDATION 1
 Image: Climate

 HDX 30
 Image: Climate

Check every 400 hours, change every 1200 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
HDX 20W-20	HDX 10W	
Check every 400 hours, change every 1200 hours		

MARSHALL ALL MODELS 302 (1982-1985)



HDX 20W-20	HDX 10W		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Normal		Moderate	
USE		CLIMATE	
Check every 50 hours, change every 800	hours		
PRODUCT RECOMMENDATION 1 HDX 30			
use Normal		сымате Tropical	
HYDRAULIC SYSTEM Capacity: 18 liter			

Check every 50 hours, change every 800 hours

GREASE POINTS/NIPPLES FREEWHEEL HUBS		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Check every 10 hours

GREASE POINTS/NIPPLES KING PINS		
USE CLIMATE		
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Check every 10 hours

GREASE POINTS/NIPPLES OTHERS		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Check every 50 hours

MARSHALL ALL MODELS 302 (1982-1985)



COOLING SYSTEM Capacity: 7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 10 hours, change every 24 months

STEERING BOX Capacity: 0,6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 400 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.