Check every 10 hours, change every 150 hours

MASSEY FERGUSON 1200 MF 1240 (1994-2002)



| ENGINE Capacity: 4,8 liter | | |
|--|-------|---------------|
| USE | | CLIMATE |
| Normal | | Tropical |
| PRODUCT RECOMMENDATION 1 | | |
| HDX 30 | | |
| Check every 10 hours, change every 150 | hours | |
| USE | | CLIMATE |
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| HDX 20W-20 | | |
| Check every 10 hours, change every 150 | hours | |
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Kroontrak MTH 10W-30 | | |

| DIFFERENTIAL FRONT (4x4) Capacity: 6,1 liter | | |
|--|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrifluid HT-Plus | Agrifluid HT | SP Gear 5015 |
| Check every 50 hours, change eve | ry 300 hours | 1 |

| TRANSAXLE/HYDRAULIC SYSTE Capacity: 23 liter | M 16/16 | |
|--|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Kroontrak CVT 10W-40 | Agrifluid HT-Plus | Kroontrak MTH 10W-30 |
| Check every 50 hours, change ever | y 300 hours | · |

MASSEY FERGUSON 1200 MF 1240 (1994-2002)



| POWER STEERING Capacity: 2,5 liter | | |
|------------------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Kroontrak CVT 10W-40 | Agrifluid HT-Plus | Kroontrak MTH 10W-30 |
| | | |

Check every 10 hours, change every 300 hours

| GREASE POINTS/NIPPLES | | |
|--------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |
| Check every 50 hours | 1 | |

| COOLING SYSTEM Capacity: 7 liter | | |
|------------------------------------|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant -38 Organic NF | Coolant -26 | |
| Check every 10 hours, change every | / 12 months | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.