

# MASSEY FERGUSON 3400 MF 3445 (2004-2010)



**ENGINE** Perkins 1104C-44T  
Capacity: 12 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1          | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3    |
|-----------------------------------|-----------------------------|-----------------------------|
| <b>Agrisynth LSP Ultra 10W-40</b> | <b>Agrisynth LSP 10W-40</b> | <b>Kroontrak CVT 10W-40</b> |

*Check every 10 hours, change every 300 hours*

**DIFFERENTIAL FRONT (4x4)**  
Capacity: 6 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |  |
|-----------------------------|------------------------------------|--|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

*Check every 300 hours, change every 1200 hours*

**HUB REDUCTIONS FRONT (4x4)**  
Capacity: 1,5 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |  |
|-----------------------------|------------------------------------|--|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

*Check every 300 hours, change every 1200 hours*

**HUB REDUCTIONS REAR HD**  
Capacity: 2,9 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1    |  |  |
|-----------------------------|--|--|
| <b>Kroontrak MTH 10W-30</b> |  |  |

*Check every 150 hours, change every 1200 hours*

**POWER TAKE OFF FRONT**  
Capacity: 0,6 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1    |  |  |
|-----------------------------|--|--|
| <b>Kroontrak MTH 10W-30</b> |  |  |

*Check every 300 hours, change every 1200 hours*

# MASSEY FERGUSON 3400 MF 3445 (2004-2010)



## TRANSAXLE/HYDRAULIC SYSTEM

Capacity: 41 liter

| USE                         |                             | CLIMATE  |
|-----------------------------|-----------------------------|----------|
| Normal                      |                             | Moderate |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2    |          |
| <b>Kroontrak CVT 10W-40</b> | <b>Kroontrak MTH 10W-30</b> |          |

Check every 150 hours, change every 1200 hours

## HYDRAULIC BRAKE SYSTEM

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>ATF Dexron II-D</b>   |  |          |

Check every 10 hours, change every 2000 hours

## GREASE POINTS/NIPPLES

| USE                      |                                 | CLIMATE                      |
|--------------------------|---------------------------------|------------------------------|
| Normal                   |                                 | Moderate                     |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

Change every 50 hours

## COOLING SYSTEM

Capacity: 17,5 liter

| USE                      |                          | CLIMATE                       |
|--------------------------|--------------------------|-------------------------------|
| Normal                   |                          | Moderate                      |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3      |
| <b>Coolant SP 15+</b>    | <b>Coolant SP 12</b>     | <b>Coolant -38 Organic NF</b> |

Check every 10 hours, change every 1200 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.