

# MASSEY FERGUSON 3600 MF 3635 (1987-1995)



**ENGINE** Perkins (quadram) 1006-6T HR2  
Capacity: 16,5 liter

| USE                               |                             | CLIMATE                     |
|-----------------------------------|-----------------------------|-----------------------------|
| Normal                            |                             | Moderate                    |
| PRODUCT RECOMMENDATION 1          | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3    |
| <b>Agrisynth LSP Ultra 10W-40</b> | <b>Agrisynth LSP 10W-40</b> | <b>Kroontrak CVT 10W-40</b> |

*Check every 10 hours, change every 250 hours*

**DIFFERENTIAL FRONT (4x4)**  
Capacity: 11 liter

| USE                         |                                    | CLIMATE  |
|-----------------------------|------------------------------------|----------|
| Normal                      |                                    | Moderate |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |          |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |          |

*Check every 100 hours, change every 1000 hours/ 12 months*

**HUB REDUCTIONS FRONT (4x4)**  
Capacity: 1,8 liter

| USE                         |                                    | CLIMATE  |
|-----------------------------|------------------------------------|----------|
| Normal                      |                                    | Moderate |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2           |          |
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |          |

*Check every 250 hours, change every 1000 hours/ 12 months*

**TRANSAXLE/HYDRAULIC SYSTEM WITH DRY CLUTCH SYSTEM 16/16**  
Capacity: 85 liter

| USE                         |  | CLIMATE  |
|-----------------------------|--|----------|
| Normal                      |  | Moderate |
| PRODUCT RECOMMENDATION 1    |  |          |
| <b>Kroontrak MTH 10W-30</b> |  |          |

*Check every 100 hours, change every 1000 hours/ 12 months*

**TRANSAXLE/HYDRAULIC SYSTEM WITH MULTI-DISC WET CLUTCH SYSTEM 16/16**  
Capacity: 85 liter

| USE                         |                                  | CLIMATE                  |
|-----------------------------|----------------------------------|--------------------------|
| Normal                      |                                  | Moderate                 |
| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2         | PRODUCT RECOMMENDATION 3 |
| <b>Kroontrak CVT 10W-40</b> | <b>Agrifluid Synth XHP Ultra</b> | <b>Agrifluid HT-Plus</b> |

*Check every 100 hours, change every 1000 hours/ 12 months*

# MASSEY FERGUSON 3600 MF 3635 (1987-1995)



## GREASE POINTS/NIPPLES

| USE                      |                                 | CLIMATE                      |
|--------------------------|---------------------------------|------------------------------|
| Normal                   |                                 | Moderate                     |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

*Check every 10 hours*

## COOLING SYSTEM

Capacity: 25 liter

| USE                           |                          | CLIMATE  |
|-------------------------------|--------------------------|----------|
| Normal                        |                          | Moderate |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2 |          |
| <b>Coolant -38 Organic NF</b> | <b>Coolant -26</b>       |          |

*Check every 100 hours, change every 1000 hours/ 12 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*