

# MASSEY FERGUSON 5400 5425 TIER II

## (2004-2008)



**ENGINE** Perkins 1104D-44T  
Capacity: 9,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Agrisynth LSP Ultra 10W-40</b>	<b>Agrisynth LSP 10W-40</b>	<b>Armado Synth LSP Ultra 10W-40</b>

*Check every 10 hours, change every 400 hours*

**DIFFERENTIAL FRONT** Carraro  
Capacity: 5,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 85W-140</b>	<b>Unigear LS GL-3/GL-5 85W-140</b>	

**DIFFERENTIAL FRONT** Dana  
Capacity: 5,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Check every 400 hours, change every 800 hours*

**HUB REDUCTIONS FRONT** Carraro  
Capacity: 0,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 85W-140</b>	<b>Unigear LS GL-3/GL-5 85W-140</b>	

*Check every 400 hours, change every 800 hours*

**HUB REDUCTIONS FRONT** Dana  
Capacity: 0,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Gearlube GL-5 80W-90</b>	<b>Unigear HS GL-3/GL-5 80W-90</b>	

*Check every 400 hours, change every 800 hours*

# MASSEY FERGUSON 5400 5425 TIER II

## (2004-2008)



### TRANSAXLE/HYDRAULIC SYSTEM 12/12

Capacity: 62 liter (Mechanical transmission), Capacity: 70 liter (Powershift)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Kroontrak CVT 10W-40***Check every 10 hours, change every 1200 hours*

### GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

**Multi Purpose Grease 3***Check every 50 hours*

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Labora Grease**

PRODUCT RECOMMENDATION 2

**Q5 MP Calcep Grease EP 2**

PRODUCT RECOMMENDATION 3

**MP Lithep Grease EP 2***Check every 50 hours*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

**Gear Grease EP 1***Check every 50 hours*

### COOLING SYSTEM

Capacity: 25 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Coolant -38 Organic NF**

PRODUCT RECOMMENDATION 2

**Coolant -26***Check every 10 hours, change every 1200 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.