

MASSEY FERGUSON 5400 5430 TIER III

(2011-2014)



ENGINE Perkins 1104D-44TA
Capacity: 9,5 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-----------------------------------|-----------------------------|--------------------------------------|
| Agrisynth LSP Ultra 10W-40 | Agrisynth LSP 10W-40 | Armado Synth LSP Ultra 10W-40 |

Check every 10 hours, change every 400 hours

| USE | CLIMATE |
|---------------|----------|
| Biodiesel B20 | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|-----------------------------------|-----------------------------|--------------------------------------|
| Agrisynth LSP Ultra 10W-40 | Agrisynth LSP 10W-40 | Armado Synth LSP Ultra 10W-40 |

Check every 10 hours, change every 400 hours

DIFFERENTIAL FRONT Dana
Capacity: 5 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|-----------------------------|------------------------------------|--|
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Check every 400 hours, change every 800 hours

HUB REDUCTIONS FRONT Dana
Capacity: 0,8 liter (each hub)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|-----------------------------|------------------------------------|--|
| Gearlube GL-5 80W-90 | Unigear HS GL-3/GL-5 80W-90 | |

Check every 400 hours, change every 800 hours

POWER TAKE OFF FRONT
Capacity: 2,5 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|--------------------------|--------------------------|--|
| SP Matic 2032 | ATF Almirol | |

Check every 10 hours, change every 400 hours

MASSEY FERGUSON 5400 5430 TIER III (2011-2014)



TRANSAXLE/HYDRAULIC SYSTEM

Capacity: 65 liter

| USE | | CLIMATE |
|-----------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Kroontrak CVT 10W-40 | | |

Check every 10 hours, change every 1200 hours

GREASE POINTS/NIPPLES

| USE | | CLIMATE |
|-------------------------------|--|----------|
| Normal | | Tropical |
| PRODUCT RECOMMENDATION 1 | | |
| Multi Purpose Grease 3 | | |

Check every 50 hours

| USE | | CLIMATE |
|--------------------------|---------------------------------|------------------------------|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

Check every 50 hours

| USE | | CLIMATE |
|--------------------------|--|---------|
| Normal | | Cold |
| PRODUCT RECOMMENDATION 1 | | |
| Gear Grease EP 1 | | |

Check every 50 hours

COOLING SYSTEM

Capacity: 23 liter

| USE | | CLIMATE |
|--------------------------|--------------------------|-------------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Coolant SP 15+ | Coolant SP 12 | Coolant -38 Organic NF |

Check every 10 hours, change every 1200 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.