

MASSEY FERGUSON 5400 5465 TIER II (2004-2008)



ENGINE Perkins 1106C-60 ETA
Capacity: 14,5 liter

USE Normal		CLIMATE Moderate
----------------------	--	----------------------------

PRODUCT RECOMMENDATION 1 Agrisynth LSP Ultra 10W-40	PRODUCT RECOMMENDATION 2 Agrisynth LSP 10W-40	PRODUCT RECOMMENDATION 3 Armado Synth LSP Ultra 10W-40
--	--	---

Check every 10 hours, change every 400 hours

DIFFERENTIAL FRONT Carraro
Capacity: 6 liter

USE Normal		CLIMATE Moderate
----------------------	--	----------------------------

PRODUCT RECOMMENDATION 1 Gearlube GL-5 85W-140	PRODUCT RECOMMENDATION 2 Unigear LS GL-3/GL-5 85W-140	
---	--	--

Check every 400 hours, change every 800 hours

DIFFERENTIAL FRONT Dana
Capacity: 6 liter

USE Normal		CLIMATE Moderate
----------------------	--	----------------------------

PRODUCT RECOMMENDATION 1 Gearlube GL-5 80W-90	PRODUCT RECOMMENDATION 2 Unigear HS GL-3/GL-5 80W-90	
--	---	--

Check every 400 hours, change every 800 hours

HUB REDUCTIONS FRONT Carraro
Capacity: 0,7 liter

USE Normal		CLIMATE Moderate
----------------------	--	----------------------------

PRODUCT RECOMMENDATION 1 Gearlube GL-5 85W-140	PRODUCT RECOMMENDATION 2 Unigear LS GL-3/GL-5 85W-140	
---	--	--

Check every 400 hours, change every 800 hours

HUB REDUCTIONS FRONT Dana
Capacity: 0,7 liter

USE Normal		CLIMATE Moderate
----------------------	--	----------------------------

PRODUCT RECOMMENDATION 1 Gearlube GL-5 80W-90	PRODUCT RECOMMENDATION 2 Unigear HS GL-3/GL-5 80W-90	
--	---	--

Check every 400 hours, change every 800 hours

MASSEY FERGUSON 5400 5465 TIER II

(2004-2008)



TRANSAXLE/HYDRAULIC SYSTEM 12/12

Capacity: 56 liter (Mechanical transmission), Capacity: 68 liter (Powershift)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Kroontrak CVT 10W-40*Check every 10 hours, change every 1200 hours*

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

Multi Purpose Grease 3*Check every 50 hours*

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2*Check every 50 hours*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

Gear Grease EP 1*Check every 50 hours*

COOLING SYSTEM

Capacity: 25 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF

PRODUCT RECOMMENDATION 2

Coolant -26*Check every 10 hours, change every 1200 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.