

# MASSEY FERGUSON 6100 MF 6120 (1995-1996)



**ENGINE** Perkins 4.41  
Capacity: 7,4 liter

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1

**Agrisynth LSP Ultra 10W-40**

PRODUCT RECOMMENDATION 2

**Agrisynth LSP 10W-40**

PRODUCT RECOMMENDATION 3

**Kroontrak CVT 10W-40**

*Change every 250 hours/ 6 months*

**DIFFERENTIAL FRONT (4x4)**  
Capacity: 6 liter

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90**

*Check every 250 hours, change every 1000 hours/ 12 months*

**HUB REDUCTIONS FRONT (4x4)**  
Capacity: 1 liter

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1

**Gearlube GL-5 80W-90**

PRODUCT RECOMMENDATION 2

**Unigear HS GL-3/GL-5 80W-90**

*Check every 250 hours, change every 1000 hours/ 12 months*

**TRANSAXLE/HYDRAULIC SYSTEM 16/16**  
Capacity: 62 liter

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1

**Kroontrak CVT 10W-40**

*Check every 100 hours, change every 1000 hours/ 12 months*

## GREASE POINTS/NIPPLES

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1

**Labora Grease**

PRODUCT RECOMMENDATION 2

**Q5 MP Calcep Grease EP 2**

PRODUCT RECOMMENDATION 3

**MP Lithep Grease EP 2**

*Check every 10 hours*

# MASSEY FERGUSON 6100 MF 6120 (1995-1996)



## COOLING SYSTEM

Capacity: 17 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Coolant -38 Organic NF**

## PRODUCT RECOMMENDATION 2

**Coolant -26**

*Check every 100 hours, change every 1000 hours/ 12 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*