

MASSEY FERGUSON 7400 7485 DYNAV TIER III (2007-2012)



ENGINE Sisu 66CTA
Capacity: 21 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrisynth LSP Ultra 10W-40	Agrisynth LSP 10W-40	Armado Synth LSP Ultra 10W-40

Check every 10 hours, change every 400 hours

DIFFERENTIAL FRONT

Capacity: 9 liter, Capacity: 8,5 liter (Suspended front axle)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 400 hours, change every 800 hours

HUB REDUCTIONS FRONT HD

Capacity: 0,8 liter, Capacity: 0,6 liter (Suspended front axle)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 400 hours, change every 800 hours

HUB REDUCTIONS REAR

Capacity: 13 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 400 hours, change every 1200 hours

TRANSAXLE

Capacity: 47-58 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Kroontrak CVT 10W-40		

Check every 10 hours, change every 2000 hours

MASSEY FERGUSON 7400 7485 DYNAV T TIER III (2007-2012)



HYDRAULIC SYSTEM

Capacity: 100 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Kroontrak CVT 10W-40*Check every 400 hours, change every 1200 hours*

CLUTCH HOUSING

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Fluid 3013*Check every 400 hours, change every 2000 hours*

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

Multi Purpose Grease 3*Check every 50 hours*

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2*Check every 50 hours*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

Gear Grease EP 1*Check every 50 hours*

MASSEY FERGUSON 7400 7485 DYNAV TIER III (2007-2012)

**COOLING SYSTEM**

Capacity: 28,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 400 hours, change every 1200 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.