

ENGINE AQ/AS Capacity: 7,3 liter		
USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Multifleet SHPD 20W-50		
Check every 10 hours, change every 250 l	hours	•
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40	
Check every 10 hours, change every 250 l	hours	- -
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Multifleet SHPD 10W-40		
Check every 10 hours, change every 250 l	hours	
ENGINE RE./RG Capacity: 7,3 liter		
USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Multifleet SHPD 20W-50		
Check every 10 hours, change every 500 l	hours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40	
Check every 10 hours, change every 500 l	hours	
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Multifleet SHPD 10W-40		
Check every 10 hours, change every 500 l	hours	



DIFFERENTIAL FRONT MFD Capacity: 5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 250 hours, change every 1000 hours

HUB REDUCTIONS FRONT MFD Capacity: 0,6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 250 hours, change every 1000 hours

POWER TAKE OFF FRONT Hydrac Capacity: 0,75 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Kroontrak MTH 10W-30	

Check every 10 hours, change every 250 hours

POWER TAKE OFF FRONT Kitchin Capacity: 0,65 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30

Check every 10 hours, change every 250 hours

TRANSAXLE/HYDRAULIC SYSTEM Capacity: 34,5-37 liter (Mechanical transmission), Capacity: 49,5 liter (XtraShift 2WD), Capacity: 52 liter (XtraShift MFD)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	Agrifluid HT-Plus	Kroontrak MTH 10W-30
Check even, 10 hours, change even, 1000	bours	

Check every 10 hours, change every 1000 hours



GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Check every 50 hours

COOLING SYSTEM Capacity: 17,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
	0.0001	

Check every 10 hours, change every 2000 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.