

MCCORMICK MTX MTX185 (2003-2007)

ENGINE BetaPower 24V
Capacity: 16 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

Multifleet SHPD 20W-50*Check every 10 hours, change every 250 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 2

Multifleet SHPD 15W-40*Check every 10 hours, change every 250 hours*

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1

Multifleet SHPD 10W-40*Check every 10 hours, change every 250 hours*

DIFFERENTIAL FRONT MFD
Capacity: 6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 85W-140

PRODUCT RECOMMENDATION 2

Unigear LS GL-3/GL-5 85W-140*Check every 250 hours, change every 500 hours*

DIFFERENTIAL FRONT INDEPENDENT FRONT SUSPENSION
Capacity: 2,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 85W-140

PRODUCT RECOMMENDATION 2

Unigear LS GL-3/GL-5 85W-140*Check every 250 hours, change every 500 hours*

MCCORMICK MTX MTX185 (2003-2007)**HUB REDUCTIONS FRONT** Independent Front Suspension

Capacity: 1,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube GL-5 85W-140****PRODUCT RECOMMENDATION 2****Unigear LS GL-3/GL-5 85W-140***Check every 250 hours, change every 500 hours***HUB REDUCTIONS FRONT** MFD

Capacity: 1,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube GL-5 85W-140****PRODUCT RECOMMENDATION 2****Unigear LS GL-3/GL-5 85W-140***Check every 250 hours, change every 500 hours***POWER TAKE OFF FRONT**

Capacity: 2,75 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Abacot MEP 220***Check every 10 hours, change every 250 hours***TRANSMISSION/HYDRAULIC SYSTEM**

Capacity: 95 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Agrifluid Synth XHP Ultra****PRODUCT RECOMMENDATION 2****Agrifluid HT-Plus****PRODUCT RECOMMENDATION 3****Kroontrak MTH 10W-30***Check every 10 hours, change every 1000 hours***GREASE POINTS/NIPPLES****USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Labora Grease****PRODUCT RECOMMENDATION 2****Q5 MP Calcep Grease EP 2****PRODUCT RECOMMENDATION 3****MP Lithep Grease EP 2***Check every 50 hours*

MCCORMICK MTX MTX185 (2003-2007)

**COOLING SYSTEM**

Capacity: 29 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Coolant -38 Organic NF****PRODUCT RECOMMENDATION 2****Coolant -26***Check every 10 hours, change every 2000 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.