PRODUCT RECOMMENDATION

# NEW HOLLAND FORD 35, FIATAGRI L FORD 4835, FIATAGRI L 65 (1996-1998)

## ENGINE Iveco 8045.06
Capacity: 11,7 liter, Filter capacity: 2,2 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---|---|---|
| **Agridiesel CRD+ 15W-40** | **Kroontrak MTH 10W-30** | **Dieselfleet LSP Ultra 10W-30** |

*Check every 10 hours, change every 300 hours*

## DIFFERENTIAL FRONT
Capacity: 4,5 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---|---|---|
| **Agrifluid HT-Plus** | **Kroontrak MTH 10W-30** | **Agrifluid HT** |

*Check every 300 hours, change every 1200 hours/ 24 months*

## HUB REDUCTIONS FRONT
Capacity: 0,8 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---|---|---|
| **Agrifluid HT-Plus** | **Kroontrak MTH 10W-30** | **Agrifluid HT** |

*Check every 300 hours, change every 1200 hours/ 24 months*

## TRANSAXLE/HYDRAULIC SYSTEM 24/12
Capacity: 49 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|---|---|---|
| **Agrifluid HT-Plus** | **Kroontrak MTH 10W-30** | **Agrifluid HT** |

*Check every 300 hours, change every 1200 hours/ 24 months*

## HYDRAULIC BRAKE SYSTEM
Capacity: 0,4 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|---|---|---|
| **LHM +** | | |

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# NEW HOLLAND FORD 35, FIATAGRI L FORD 4835, FIATAGRI L 65 (1996-1998)

## POWER STEERING
Capacity: 2 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | **PRODUCT RECOMMENDATION 3** |
| **Agrifluid HT-Plus** | **Kroontrak MTH 10W-30** | **Agrifluid HT** |

*Check every 10 hours, change every 1200 hours/ 12 months*

## GREASE POINTS/NIPPLES

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | |
| **Q5 MP Calcep Grease EP 2** | **MP Lithep Grease EP 2** | |

*Change every 50 hours*

## COOLING SYSTEM
Capacity: 14 liter, Capacity: 16 liter (+ cabin)

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | |
| **Coolant SP 15+** | **Coolant SP 12** | |

*Check every 10 hours, change every 1200 hours/ 24 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367