

# NEW HOLLAND T6000 T6020 DELTA (2007-2012)



**ENGINE** Tier III  
Capacity: 10 liter

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1  
**Agridiesel MSP 15W-40**

PRODUCT RECOMMENDATION 2  
**Agridiesel CRD+ 15W-40**

PRODUCT RECOMMENDATION 3  
**Armado Synth 5W-30**

*Check every 10 hours, change every 600 hours*

**DIFFERENTIAL FRONT**  
Capacity: 9 liter

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1  
**Agrifluid HT-Plus**

PRODUCT RECOMMENDATION 2  
**Kroontrak MTH 10W-30**

PRODUCT RECOMMENDATION 3  
**Agrifluid HT**

*Check every 300 hours, change every 1200 hours/ 12 months*

**HUB REDUCTIONS FRONT**  
Capacity: 1,5 liter, Capacity: 3 liter (+ front brakes)

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1  
**Agrifluid HT-Plus**

PRODUCT RECOMMENDATION 2  
**Kroontrak MTH 10W-30**

PRODUCT RECOMMENDATION 3  
**Agrifluid HT**

*Check every 300 hours, change every 1200 hours/ 12 months*

**POWER TAKE OFF FRONT**  
Capacity: 0,4 liter

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1  
**Agrifluid HT-Plus**

PRODUCT RECOMMENDATION 2  
**Kroontrak MTH 10W-30**

PRODUCT RECOMMENDATION 3  
**Agrifluid HT**

*Check every 300 hours, change every 1200 hours/ 12 months*

**TRANSAXLE/HYDRAULIC SYSTEM**  
Capacity: 58,5-65,5 liter (Dual Command), Capacity: 55-62 liter (Electro Command), Capacity: 58-65 liter (Synchro Command)

USE  
Normal

CLIMATE  
Moderate

PRODUCT RECOMMENDATION 1  
**Agrifluid HT-Plus**

PRODUCT RECOMMENDATION 2  
**Kroontrak MTH 10W-30**

PRODUCT RECOMMENDATION 3  
**Agrifluid HT**

*Check every 300 hours, change every 1200 hours/ 12 months*

# NEW HOLLAND T6000 T6020 DELTA (2007-2012)



## HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>LHM +</b>		

## GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Q5 MP Calcep Grease EP 2</b>	<b>MP Lithep Grease EP 2</b>	

*Change every 50 hours*

## COOLING SYSTEM

Capacity: 21 liter, Capacity: 23 liter (+ cabin)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	

*Check every 10 hours, change every 1200 hours/ 24 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*