

NEW HOLLAND T8000 T8050 (2007-2011)

ENGINE New Holland Tier III
Capacity: 21 liter, Filter capacity: 2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40

Check every 10 hours, change every 300 hours

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Armado Synth 5W-30	Dieselfleet LSP Ultra 10W-30	

Check every 10 hours, change every 300 hours

DIFFERENTIAL FRONT WITH 10 BOLTS
Capacity: 12,3 liter (Standard), Capacity: 13,25 liter (Supersteer)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube Racing 75W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 300 hours, change every 1200 hours/ 12 months

DIFFERENTIAL FRONT WITH 12 BOLTS
Capacity: 11,8 liter (Standard), Capacity: 13,25 liter (Supersteer)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube Racing 75W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 300 hours, change every 1200 hours/ 12 months

HUB REDUCTIONS FRONT WITH 10 BOLTS
Capacity: 1,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

Check every 300 hours, change every 1200 hours/ 12 months

NEW HOLLAND T8000 T8050 (2007-2011)**HUB REDUCTIONS FRONT WITH 12 BOLTS**

Capacity: 3,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 85W-140	Unigear LS GL-3/GL-5 85W-140	

*Check every 300 hours, change every 1200 hours/ 12 months***TRANSAXLE/HYDRAULIC SYSTEM**

Capacity: 172 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT-Plus		

*Check every 10 hours, change every 1500 hours***GREASE POINTS/NIPPLES**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	

*Change every 50 hours***COOLING SYSTEM**

Capacity: 26,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Check every 10 hours, change every 2100 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.