

NEW HOLLAND TD-D TD 55D (2004-2008)**ENGINE**

Capacity: 7,3 liter, Filter capacity: 0,6 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Agridiesel CRD+ 15W-40****PRODUCT RECOMMENDATION 2****Kroontrak MTH 10W-30****PRODUCT RECOMMENDATION 3****Dieselfleet LSP Ultra 10W-30***Check every 10 hours, change every 300 hours***DIFFERENTIAL FRONT**

Capacity: 4,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Agrifluid HT-Plus****PRODUCT RECOMMENDATION 2****Kroontrak MTH 10W-30****PRODUCT RECOMMENDATION 3****Agrifluid HT***Check every 300 hours, change every 1200 hours/ 24 months***HUB REDUCTIONS FRONT**

Capacity: 0,8 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Agrifluid HT-Plus****PRODUCT RECOMMENDATION 2****Kroontrak MTH 10W-30****PRODUCT RECOMMENDATION 3****Agrifluid HT***Check every 300 hours, change every 1200 hours/ 24 months***TRANSAXLE/HYDRAULIC SYSTEM/POWER STEERING 12/12**

Capacity: 49 liter, Capacity: 55 liter (Synchro reverser)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Agrifluid HT-Plus****PRODUCT RECOMMENDATION 2****Kroontrak MTH 10W-30****PRODUCT RECOMMENDATION 3****Agrifluid HT***Check every 300 hours, change every 1200 hours/ 24 months***HYDROSTATIC STEERING**

Capacity: 2 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Agrifluid HT-Plus****PRODUCT RECOMMENDATION 2****Kroontrak MTH 10W-30****PRODUCT RECOMMENDATION 3****Agrifluid HT***Check every 10 hours, change every 1200 hours*

NEW HOLLAND TD-D TD 55D (2004-2008)**HYDRAULIC BRAKE SYSTEM**

Capacity: 0,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
LHM +		

*Check every 10 hours***GREASE POINTS/NIPPLES**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	

*Check every 50 hours***COOLING SYSTEM**

Capacity: 12 liter, Capacity: 14 liter (+ cabin)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Check every 50 hours, change every 1200 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.