PRODUCT RECOMMENDATION

NEW HOLLAND TL-A TL100A (2004-2007)

ENGINE Tier II
Capacity: 9,5 liter, Filter capacity: 0,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel MSP 15W-40	**Agridiesel CRD+ 15W-40**	**Armado Synth 5W-30**

Check every 10 hours, change every 600 hours

DIFFERENTIAL FRONT
Capacity: 7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	**Kroontrak MTH 10W-30**	**Agrifluid HT**

Check every 300 hours, change every 1200 hours/ 24 months

HUB REDUCTIONS FRONT
Capacity: 1,25 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	**Kroontrak MTH 10W-30**	**Agrifluid HT**

Check every 300 hours, change every 1200 hours/ 24 months

TRANSAXLE/HYDRAULIC SYSTEM
Capacity: 55 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	**Kroontrak MTH 10W-30**	**Agrifluid HT**

Check every 300 hours, change every 1200 hours/ 24 months

HYDROSTATIC DRIVE
Capacity: 2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	**Kroontrak MTH 10W-30**	**Agrifluid HT**

Check every 300 hours, change every 1200 hours/ 24 months

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

NEW HOLLAND TL-A TL100A (2004-2007)

HYDRAULIC BRAKE SYSTEM
Capacity: 0,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
LHM +		

Check every 10 hours, change every 1200 hours/ 24 months

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Q5 MP Calcep Grease EP 2	**MP Lithep Grease EP 2**	

Check every 50 hours

COOLING SYSTEM
Capacity: 14 liter, Capacity: 16 liter (+ cabin)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Coolant SP 15+	**Coolant SP 12**	

Check every 10 hours, change every 1200 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367