

## NEW HOLLAND TM TM 150 (2000-2002)



**ENGINE** NH 675/WV  
Capacity: 19 liter

| USE                           |                             | CLIMATE                  |
|-------------------------------|-----------------------------|--------------------------|
| Normal                        |                             | Moderate                 |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3 |
| <b>Agridiesel CRD+ 15W-40</b> | <b>Kroontrak MTH 10W-30</b> | <b>Asyntho 5W-30</b>     |

*Check every 10 hours, change every 300 hours*

**DIFFERENTIAL FRONT**  
Capacity: 14 liter

| USE                      |                             | CLIMATE                  |
|--------------------------|-----------------------------|--------------------------|
| Normal                   |                             | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3 |
| <b>Agrifluid HT-Plus</b> | <b>Kroontrak MTH 10W-30</b> | <b>Agrifluid HT</b>      |

*Check every 300 hours, change every 1200 hours/ 12 months*

**HUB REDUCTIONS FRONT**  
Capacity: 2,15 liter

| USE                      |                             | CLIMATE                  |
|--------------------------|-----------------------------|--------------------------|
| Normal                   |                             | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3 |
| <b>Agrifluid HT-Plus</b> | <b>Kroontrak MTH 10W-30</b> | <b>Agrifluid HT</b>      |

*Check every 300 hours, change every 1200 hours/ 12 months*

**TRANSAXLE/HYDRAULIC SYSTEM** PowerCommand 17/6  
Capacity: 100 liter

| USE                      |                             | CLIMATE                  |
|--------------------------|-----------------------------|--------------------------|
| Normal                   |                             | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3 |
| <b>Agrifluid HT-Plus</b> | <b>Kroontrak MTH 10W-30</b> | <b>Agrifluid HT</b>      |

*Check every 300 hours, change every 1200 hours/ 12 months*

**TRANSAXLE/HYDRAULIC SYSTEM** Range Command 17/6  
Capacity: 90 liter

| USE                      |                             | CLIMATE                  |
|--------------------------|-----------------------------|--------------------------|
| Normal                   |                             | Moderate                 |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2    | PRODUCT RECOMMENDATION 3 |
| <b>Agrifluid HT-Plus</b> | <b>Kroontrak MTH 10W-30</b> | <b>Agrifluid HT</b>      |

*Check every 300 hours, change every 1200 hours/ 12 months*

**NEW HOLLAND TM TM 150 (2000-2002)****HYDRAULIC BRAKE SYSTEM**

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**LHM +****GREASE POINTS/NIPPLES**

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**MoS2 Grease EP 2***Change every 50 hours***COOLING SYSTEM**

Capacity: 23,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**Coolant SP 15+**

PRODUCT RECOMMENDATION 2

**Coolant SP 12***Check every 10 hours, change every 1200 hours/ 24 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*