NEW HOLLAND TN-SA TN60SA (2004-2008)



| ENGINE Tier II Capacity: 7,5 liter, Filter capacity: 0,8 liter | |
|---|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Kroontrak MTH 10W-30 | |

| DIFFERENTIAL FRONT Capacity: 4,5 liter | | |
|---|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrifluid HT-Plus | Kroontrak MTH 10W-30 | Agrifluid HT |

| HUB REDUCTIONS FRONT Capacity: 1 liter, Capacity: 1,5 liter (+ from | nt brakes) | |
|---|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrifluid HT-Plus | Kroontrak MTH 10W-30 | Agrifluid HT |

| TRANSAXLE/HYDRAULIC SYSTE Capacity: 42-49 liter | М | | |
|--|--------------------------|--------------------------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 | |
| Agrifluid HT-Plus | Kroontrak MTH 10W-30 | Agrifluid HT | |

| HYDRAULIC BRAKE SYSTEM Capacity: 0,7 liter, Capacity: 1,2 liter (+ fro | nt brakes) | |
|--|------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| LHM + | | |
| | | |

NEW HOLLAND TN-SA TN60SA (2004-2008)



| GREASE POINTS/NIPPLES | | |
|--------------------------|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 | |

| COOLING SYSTEM Capacity: 10 liter, Capacity: 12 liter | (+ cabin) | | |
|---|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Coolant SP 15+ | Coolant SP 12 | | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.