NEW HOLLAND TND/S TN 55 D/S (1998-2003)



ENGINE Iveco 8035.05 Capacity: 7,5 liter, Filter capacity: 0,8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agridiesel CRD+ 15W-40	Kroontrak MTH 10W-30	Asyntho 5W-30

Check every 10 hours, change every 300 hours/12 months

DIFFERENTIAL FRONT Capacity: 4,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT
Check every 300 hours, change ev	very 1200 hours/ 24 months	

HUB REDUCTIONS FRONT Capacity: 0,8 liter, Capacity: 1,3 liter (+ front brakes)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT
Charles and 200 have about		

Check every 300 hours, change every 1200 hours/24 months

TRANSAXLE/HYDRAULIC SYSTE Capacity: 42 liter	EM 16/16	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT
Check every 50 hours, change eve	ery 1200 hours/ 24 months	

HYDRAULIC BRAKE SYSTEM Capacity: 0,7 liter, Capacity: 0,5 liter (+ front brakes)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
LHM +		
Check every 50 hours		

NEW HOLLAND TND/S TN 55 D/S (1998-2003)



USE		CLIMATE	
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2		

Check every 50 hours

information contained herein is subject to changes without notification.

GREASE POINTS/NIPPLES WHEEL BEARINGS		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		
Check every 300 hours	·	

COOLING SYSTEM Capacity: 10 liter, Capacity: 12 liter	(+ cabin)	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	
Check every 10 hours, change eve	ry 1200 hours/24 months	'

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the

KROON-OIL B.V. Postbus 149 7600 AC Almelo