NEW HOLLAND TNF TN 95 F (2002-2008)



| ENGINE New Holland Capacity: 10,5 liter, Filter capacity: 1 liter | | |
|--|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Agridiesel CRD+ 15W-40 | Multifleet SHPD 15W-40 | |

Check every 10 hours, change every 300 hours

| DIFFERENTIAL FRONT Capacity: 2,8 liter | | |
|---|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrifluid HT-Plus | Kroontrak MTH 10W-30 | Agrifluid HT |
| Chaok ayan, 200 bayna abanga ay | | |

Check every 300 hours, change every 1200 hours/ 24 months

| HUB REDUCTIONS FRONT Capacity: 1,75 liter (+ front brakes), Capacity: 1 liter (Without brakes) | | | |
|--|--------------------------|--------------------------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 | |
| Agrifluid HT-Plus | Kroontrak MTH 10W-30 | Agrifluid HT | |
| | | | |

Check every 300 hours, change every 1200 hours/24 months

| TRANSAXLE/HYDRAULIC SYSTEM 24/12 Capacity: 44 liter | | |
|---|---------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrifluid HT-Plus | Kroontrak MTH 10W-30 | Agrifluid HT |
| Check every 300 hours, change ev | ery 1200 hours/ 24 months | |

| HYDRAULIC BRAKE SYSTEM Capacity: 0,5 liter, Capacity: 0,2 liter (+ front brakes) | | |
|--|----------|--|
| USE | CLIMATE | |
| Normal | Moderate | |
| PRODUCT RECOMMENDATION 1 | | |
| LHM + | | |
| Check every 50 hours, change every 1200 hours/ 24 | months | |

NEW HOLLAND TNF TN 95 F (2002-2008)



| | ' | <u> </u> |
|--------------------------|--------------------------|----------|
| Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Normal | | Moderate |
| USE | | CLIMATE |
| GREASE POINTS/NIPPLES | | |

Check every 50 hours

| COOLING SYSTEM Capacity: 13,5 liter (+ cabin), Capacity: 11,5 liter (Without cabin) | | | |
|---|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Coolant SP 15+ | Coolant SP 12 | | |
| Check every 10 hours, change every 1200 hours/24 months | | | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.