

NEW HOLLAND TVT TVT145 (2004-2007)



ENGINE CNH 6600 Tier II
Capacity: 20 liter

USE
Extended

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1
Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 2
Multifleet SHPD 15W-40

PRODUCT RECOMMENDATION 3
Multifleet SHPD 20W-50

Check every 10 hours, change every 500 hours/ 12 months

USE
Extended

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Multifleet SHPD 10W-40

Check every 10 hours, change every 500 hours/ 12 months

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Kroontrak CVT 10W-40

PRODUCT RECOMMENDATION 2
Agridiesel CRD+ 15W-40

Check every 10 hours, change every 250 hours/ 12 months

DIFFERENTIAL FRONT

Capacity: 2,2 liter (20.25 suspension), Capacity: 5,5 liter (20.29 suspension), Capacity: 8 liter (Standard)

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2
Unigear HS GL-3/GL-5 80W-90

PRODUCT RECOMMENDATION 3
Gearlube GL-5 85W-140

Check every 250 hours, change every 1000 hours/ 12 months

HUB REDUCTIONS FRONT + BRAKES

Capacity: 2 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Agrifluid HT-Plus

PRODUCT RECOMMENDATION 2
Kroontrak MTH 10W-30

PRODUCT RECOMMENDATION 3
Agrifluid HT

Check every 250 hours, change every 1000 hours/ 12 months

NEW HOLLAND TVT TVT145 (2004-2007)**HUB REDUCTIONS FRONT WITHOUT BRAKES**

Capacity: 1,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	Gearlube GL-5 85W-140

*Check every 250 hours, change every 1000 hours/ 12 months***HUB REDUCTIONS REAR**

Capacity: 10 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	Gearlube GL-5 85W-140

*Check every 250 hours, change every 1000 hours/ 12 months***POWER TAKE OFF FRONT**

Capacity: 3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	Gearlube LS 80W-90

*Check every 250 hours, change every 1000 hours/ 12 months***TRANSAXLE/HYDRAULIC SYSTEM AutoCommand**

Capacity: 60 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Kroontrak CVT 10W-40		

*Check every 250 hours, change every 1000 hours/ 12 months***HYDRAULIC SYSTEM + POWER STEERING**

Capacity: 52 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
ATF Dexron II-D	Perlus H 46	Perlus AF 46

Check every 250 hours, change every 1000 hours/ 12 months

NEW HOLLAND TVT TVT145 (2004-2007)**HYDRAULIC BRAKE SYSTEM**

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

LHM +

Check every 250 hours, change every 2000 hours/ 24 months

COOLING SYSTEM

Capacity: 25 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 15+

PRODUCT RECOMMENDATION 2

Coolant SP 12

Check every 250 hours, change every 1000 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.