

# RANSOMES HIGHWAY HIGHWAY 3

## 2WD/4WD LGEA320/LGEA340



**ENGINE** Kubota D1105-T-E3B  
Capacity: 6,4 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

**Multifleet SCD 30***Check every 10 hours, change every 250 hours*

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Multifleet SCD 20W-20***Check every 10 hours, change every 250 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Kroontrak MTH 10W-30**

PRODUCT RECOMMENDATION 2

**Multifleet SHPD 10W-40***Check every 10 hours, change every 250 hours*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

**Multifleet SCD 10W***Check every 10 hours, change every 250 hours*

USE	CLIMATE
First change only	Tropical

PRODUCT RECOMMENDATION 1

**Multifleet SCD 30***Change every 50 hours*

USE	CLIMATE
First change only	Mediterranean

PRODUCT RECOMMENDATION 1

**Multifleet SCD 20W-20***Change every 50 hours*

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1

**Kroontrak MTH 10W-30**

PRODUCT RECOMMENDATION 2

**Multifleet SHPD 10W-40***Change every 50 hours*

# RANSOMES HIGHWAY HIGHWAY 3

## 2WD/4WD LGEA320/LGEA340



USE		CLIMATE
First change only		Arctic
PRODUCT RECOMMENDATION 1		
<b>Multifleet SCD 10W</b>		
<i>Change every 50 hours</i>		

TRANSAXLE HYDROSTATIC Capacity: 36 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Perlus H 46</b>	<b>Perlus AF 46</b>	
<i>Check every 10 hours, change every 1000 hours/ 12 months</i>		

COOLING SYSTEM Capacity: 5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	
<i>Check every 10 hours, change every 1000 hours/ 12 months</i>		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.