## **RENAULT 100 421 M** (1977-1985)



**ENGINE** MWM D 327-3

Capacity: 8,3 liter, Filter capacity: 1 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

## TRANSAXLE/HYDRAULIC SYSTEM 10/2

Capacity: 26,5 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

| GREASE POINTS/NIPPLES OTHERS |                          |          |  |  |
|------------------------------|--------------------------|----------|--|--|
| USE                          |                          | CLIMATE  |  |  |
| Normal                       |                          | Moderate |  |  |
| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2 |          |  |  |
| Q5 MP Calcep Grease EP 2     | MP Lithep Grease EP 2    |          |  |  |
| Check every 50 hours         | '                        | '        |  |  |

| GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT |                          |          |  |  |
|--|--------------------------|----------|--|--|
| USE  |                          | CLIMATE  |  |  |
| Normal                                     |                          | Moderate |  |  |
| PRODUCT RECOMMENDATION 1                   | PRODUCT RECOMMENDATION 2 |          |  |  |
| Q5 MP Calcep Grease EP 2                   | MP Lithep Grease EP 2    |          |  |  |
| Check every 200 hours                      |                          |          |  |  |

## **BELT PULLEY**

Capacity: 0,8 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

| STEERING BOX<br>Capacity: 0,3 liter |                              |          |
|-------------------------------------|------------------------------|----------|
| USE                                 |                              | CLIMATE  |
| Normal                              |                              | Moderate |
| PRODUCT RECOMMENDATION 1            | PRODUCT RECOMMENDATION 2     |          |
| Gearlube GL-5 85W-140               | Unigear LS GL-3/GL-5 85W-140 |          |
| Check every 200 hours               |                              |          |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.