

RENAULT CERES CERES 95-, 95X 4WD (1993-1995)

**ENGINE** MWM D 226-4

Capacity: 11,3 liter, Filter capacity: 0,75 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

DIFFERENTIAL FRONT (4x4)

Capacity: 6 liter

| USE | | CLIMATE |
|--|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Agrifluid HT | | |
| <i>Check every 100 hours, change every 800 hours</i> | | |

HUB REDUCTIONS FRONT (4x4)

Capacity: 0,7 liter

| USE | | CLIMATE |
|--|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Agrifluid HT | | |
| <i>Check every 100 hours, change every 800 hours</i> | | |

POWER TAKE OFF FRONT

Capacity: 0,5 liter

| USE | | CLIMATE |
|-------------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Agrifluid HT | | |
| <i>Change every 100 hours</i> | | |

TRANSAXLE/HYDRAULIC SYSTEM 10/10

Capacity: 54 liter

| USE | | CLIMATE |
|--|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Agrifluid HT | | |
| <i>Check every 10 hours, change every 800 hours/ 12 months</i> | | |

RENAULT CERES CERES 95-, 95X 4WD

(1993-1995)



HYDRAULIC BRAKE SYSTEM

Capacity: 0,9 liter

| USE | | CLIMATE |
|----------------------------------|---------------------------|--------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | Drauliquid DOT 3 |

Change every 600 hours/ 12 months

GREASE POINTS/NIPPLES 3-POINT HITCH

| USE | | CLIMATE |
|---------------------------------|------------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 | |

Check every 50 hours

GREASE POINTS/NIPPLES OTHERS

| USE | | CLIMATE |
|---------------------------------|------------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 | |

Check every 100 hours

COOLING SYSTEM

Capacity: 12,5 liter

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Coolant SP 16 | | |

Change every 600 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.