

RENAULT CERGOS CERGOS 350 (1997-2003)



ENGINE DPS 4045 T
Capacity: 11 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 2

Multifleet SHPD 15W-40

Check every 10 hours, change every 200 hours

DIFFERENTIAL FRONT (4x4)
Capacity: 5,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90

Check every 200 hours, change every 800 hours/ 12 months

HUB REDUCTIONS FRONT (4x4)
Capacity: 0,6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90

Check every 200 hours, change every 800 hours/ 12 months

POWER TAKE OFF FRONT
Capacity: 0,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90

Check every 10 hours, change every 200 hours

TRANSAXLE/HYDRAULIC SYSTEM 20/20
Capacity: 65 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agrifluid HT

Check every 10 hours, change every 800 hours/ 12 months

RENAULT CERGOS CERGOS 350 (1997-2003)



HYDRAULIC BRAKE SYSTEM

Capacity: 0,9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid DOT 5.1	Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4

Check every 600 hours, change every 800 hours/ 12 months

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	

Check every 50 hours

COOLING SYSTEM

Capacity: 13,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 16		

Check every 10 hours, change every 1200 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.