## **RENAULT LB, F, V, EV 70-12, 70-14 V** (1990-1998)



<b>ENGINE</b> Deutz F4L-912 Capacity: 9 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agridiesel CRD+ 15W-40	Multifleet SHPD 15W-40	

Check every 10 hours, change every 100 hours

<b>DIFFERENTIAL FRONT</b> (4x4) Capacity: 4 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT	
01 1 501 1	

Check every 50 hours, change every 1200 hours

HUB REDUCTIONS FRONT (4x4) Capacity: 0,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT	
Check every 50 hours, change every 1200 hours	

TRANSAXLE/HYDRAULIC SYSTEM 12/12 Capacity: 31 liter		
use Normal		climate Moderate
PRODUCT RECOMMENDATION 1 Agrifluid HT		

Check every 10 hours, change every 1200 hours

GREASE POINTS/NIPPLES OTHERS			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	
Check every 50 hours			

## **RENAULT LB, F, V, EV 70-12, 70-14 V** (1990-1998)



GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	
Check every 200 hours		·	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.