## RENAULT MX, MS, MA, ME, PX, PS, PA, PE 65-32 ME, MA, MS, MX (1989-1994)



**ENGINE** MWM D 226-3 Capacity: 7,75 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

TRANSAXLE/HYDRAULIC SYSTEM 12/12 Capacity: 46 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Check every 10 hours, change every	800 hours/ 12 months	'

USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1 Agrifluid HT	

Check every 10 hours, change every 800 hours/ 12 months

GREASE POINTS/NIPPLES				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2		
Check every 50 hours		·		

GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT				
use Normal		climate Moderate		
			PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2		
Check every 200 hours				

## RENAULT MX, MS, MA, ME, PX, PS, PA, PE 65-32 ME, MA, MS, MX (1989-1994)



COOLING SYSTEM Capacity: 9,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 16	
Check every 10 hours, change every 600	urs

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.