

RENAULT TA, TE, TL, TS, TX, TZ 133-14 TX (1981-1987)

**ENGINE** MWM D 226-6

Capacity: 14,8 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Kroontrak MTH 10W-30***Check every 10 hours, change every 100 hours***DIFFERENTIAL FRONT (4x4)**

Capacity: 4,2 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

HUB REDUCTIONS FRONT (4x4)

Capacity: 1,4 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

POWER TAKE OFF FRONT

Capacity: 0,8 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

TRANSAXLE/HYDRAULIC SYSTEM 16/16

Capacity: 58 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

HYDRAULIC BRAKE SYSTEM

Capacity: 0,9 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Drauliquid-LV Super DOT 4****PRODUCT RECOMMENDATION 2****Drauliquid-S DOT 4****PRODUCT RECOMMENDATION 3****Drauliquid DOT 3***Change every 600 hours/ 12 months***GREASE POINTS/NIPPLES****USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Q5 MP Calcep Grease EP 2****PRODUCT RECOMMENDATION 2****MP Lithep Grease EP 2***Check every 50 hours*

RENAULT TA, TE, TL, TS, TX, TZ 133-14 TX (1981-1987)



GREASE POINTS/NIPPLES WHEEL BEARINGS REAR

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	

Check every 200 hours

COOLING SYSTEM

Capacity: 23 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 16		

Change every 600 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.