RENAULT TA, TE, TL, TS, TX, TZ 160-94 TZ (1993-1997)



ENGINE MWM TD 228-6B6 Capacity: 17 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Kroontrak MTH 10W-30	

Check every 10 hours, change every 200 hours

DIFFERENTIAL FRONT (4x4) Capacity: 4,2 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT	

Check every 100 hours, change every 800 hours/ 12 months

HUB REDUCTIONS FRONT (4x4) Capacity: 1,35 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		

Check every 50 hours, change every 800 hours/ 12 months

POWER TAKE OFF FRONT Capacity: 0,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT	

Change every 100 hours

TRANSAXLE/HYDRAULIC SYSTEM 27/27 Capacity: 120 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		

Check every 10 hours, change every 800 hours/ 12 months

RENAULT TA, TE, TL, TS, TX, TZ 160-94 TZ (1993-1997)



HYDRAULIC BRAKE SYSTEM Capacity: 1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
Charly avery 50 hours, abanga avery 600 hours/12 months		

Check every 50 hours, change every 600 hours/ 12 months

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Check every 50 hours

COOLING SYSTEM Capacity: 24,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 16		
Check every 10 hours, change every 600 hours/ 12 months		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.