## SAME ANCIENT MODELS HERCULES 160 (1980-1984)



ENGINE Same DA1056PT Capacity: 16,2 liter		
USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Multifleet SCD 40		
Check every 10 hours, change every 125	hours	
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		
Check every 10 hours, change every 125	hours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SHPD 15W-40		
Check every 10 hours, change every 125	hours	
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Multifleet SCD 20W-20		
Check every 10 hours, change every 125	hours	
<b>DIFFERENTIAL FRONT</b> (4x4) Capacity: 20 liter		
USE		CLIMATE
Normal		Moderate

PRODUCT RECOMMENDATION 1

## Agrifluid HT

Check every 125 hours, change every 1000 hours

HUB REDUCTIONS FRONT (4x4) Capacity: 3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Check every 125 hours change every 100	0 hours	

Check every 125 hours, change every 1000 hours

## SAME ANCIENT MODELS HERCULES 160 (1980-1984)



TRANSAXLE MANUAL 12/4 Capacity: 101 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Agrifluid HT	
01 1 1051 1 000	

Check every 125 hours, change every 3000 hours

AUXILIARY HYDRAULIC SYSTEM Capacity: 30 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
Check every 125 hours, change every 300	0 hours	

HYDRAULIC SYSTEM Capacity: 23 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Chack overy 125 hours chapped overy 200	0 hours	

Check every 125 hours, change every 3000 hours

HYDRAULIC BRAKE SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	

POWER STEERING Capacity: 2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
Check every 125 hours, change every 100	0 hours	•

## SAME ANCIENT MODELS HERCULES 160 (1980-1984)



	CLIMATE
	Moderate
PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Check every 20 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.