## SAME ANCIENT MODELS LEOPARD 90 TURBO (1982-1986)



ENGINE Same 1054PT Capacity: 10,2 liter		
USE		CLIMATE
Normal		Tropical
PRODUCT RECOMMENDATION 1		
Multifleet SCD 40		
Check every 10 hours, change every 125	hours	
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		
Check every 10 hours, change every 125	hours	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SHPD 15W-40		
Check every 10 hours, change every 125	hours	
USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Multifleet SCD 20W-20		
Check every 10 hours, change every 125	hours	
<b>DIFFERENTIAL FRONT</b> (4x4) Capacity: 5,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		

HUB REDUCTIONS FRONT (4x4) Capacity: 2,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Check every 125 hours, change every 1000 hours		

**Agrifluid HT** 

Check every 125 hours, change every 1000 hours

## SAME ANCIENT MODELS LEOPARD 90 TURBO (1982-1986)



TRANSAXLE MANUAL 24/12 Capacity: 66 liter	
use Normal	climate Moderate
PRODUCT RECOMMENDATION 1 Agrifluid HT	

Check every 125 hours, change every 3000 hours

HYDRAULIC SYSTEM Capacity: 20 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Agrifluid HT		
Check every 125 hours, change every	3000 hours	

HYDRAULIC BRAKE SYSTEM

USE CLIMATE

Normal Moderate

PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2

ATF Dexron II-D ATF-A

POWER STEERING Capacity: 2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
ATF Dexron II-D	ATF-A	
Check every 125 hours, change every 1000 hours		

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Check every 20 hours	<u> </u>	<u> </u>

## SAME ANCIENT MODELS LEOPARD 90 TURBO (1982-1986)



GREASE POINTS/NIPPLES WHEEL BEARINGS FRONT		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Change every 1000 hours		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.