

# SAME DIAMOND DIAMOND 270 DCR -> WSXJ370200LS10001 (2008 AND AFTER)



**ENGINE** Deutz TCD 2013 L06 4V DCR  
Capacity: 29 liter, Filter capacity: 1 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2     | PRODUCT RECOMMENDATION 3      |
|-----------------------------|------------------------------|-------------------------------|
| <b>Agrisynth LSP 10W-40</b> | <b>Agridiesel MSP 15W-40</b> | <b>Agridiesel CRD+ 15W-40</b> |

*Check every 10 hours, change every 500 hours/ 12 months*

| USE            | CLIMATE  |
|----------------|----------|
| Biodiesel B100 | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2     | PRODUCT RECOMMENDATION 3      |
|-----------------------------|------------------------------|-------------------------------|
| <b>Agrisynth LSP 10W-40</b> | <b>Agridiesel MSP 15W-40</b> | <b>Agridiesel CRD+ 15W-40</b> |

*Check every 10 hours, change every 250 hours/ 12 months*

**CLUTCH FOR TURBOCOMPRESSOR**  
Capacity: 13 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

**DIFFERENTIAL FRONT**  
Capacity: 8,5 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1  |  |  |
|---------------------------|--|--|
| <b>Gearlube LS 80W-90</b> |  |  |

*Check every 250 hours, change every 1000 hours/ 12 months*

**HUB REDUCTIONS FRONT**  
Capacity: 1,9 liter (each hub)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1  |  |  |
|---------------------------|--|--|
| <b>Gearlube LS 80W-90</b> |  |  |

*Check every 250 hours, change every 1000 hours/ 12 months*

**HUB REDUCTIONS REAR**  
Capacity: 12 liter (each hub)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1  |  |  |
|---------------------------|--|--|
| <b>Gearlube LS 80W-90</b> |  |  |

*Check every 250 hours, change every 1000 hours/ 12 months*

# SAME DIAMOND DIAMOND 270 DCR -> WSXJ370200LS10001 (2008 AND AFTER)



## POWER TAKE OFF FRONT

Capacity: 1,85 liter

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>Agrifluid HT-Plus</b> | <b>Agrifluid HT</b>      |          |

*Check every 250 hours, change every 500 hours*

## TRANSAXLE/TRANSMISSION

Capacity: 79 liter (Rigid rear axle), Capacity: 81 liter (Suspended rear axle)

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>Agrifluid HT-Plus</b> | <b>Agrifluid HT</b>      |          |

*Check every 50 hours, change every 1000 hours/ 12 months*

## AUXILIARY HYDRAULIC SYSTEM

Capacity: 45-75 liter

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>Agrifluid HT-Plus</b> | <b>Agrifluid HT</b>      |          |

*Check every 50 hours, change every 1000 hours/ 12 months*

## HYDRAULIC BRAKE SYSTEM

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>SP Matic 2032</b>     |  |          |

*Change every 24 months*

## GREASE POINTS/NIPPLES

| USE                      |                                 | CLIMATE                      |
|--------------------------|---------------------------------|------------------------------|
| Normal                   |                                 | Moderate                     |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

*Change every 50 hours*

# SAME DIAMOND DIAMOND 270 DCR -> WSXJ370200LS10001 (2008 AND AFTER)

**COOLING SYSTEM**

Capacity: 36 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Coolant SP 12 EVO</b> |  |          |

Check every 10 hours, change every 1000 hours/ 12 months

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*