

SAME DIAMOND DIAMOND 270 DCR -> WSXL910200LS10001 (2008 AND AFTER)



ENGINE Deutz TCD 2013 L06 4V DCR
Capacity: 29 liter, Filter capacity: 1 liter

USE Normal		CLIMATE Moderate
----------------------	--	----------------------------

PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40	PRODUCT RECOMMENDATION 2 Agridiesel MSP 15W-40	PRODUCT RECOMMENDATION 3 Agridiesel CRD+ 15W-40
--	---	--

Check every 10 hours, change every 500 hours/ 12 months

USE Biodiesel B100		CLIMATE Moderate
------------------------------	--	----------------------------

PRODUCT RECOMMENDATION 1 Agrisynth LSP 10W-40	PRODUCT RECOMMENDATION 2 Agridiesel MSP 15W-40	PRODUCT RECOMMENDATION 3 Agridiesel CRD+ 15W-40
--	---	--

Check every 10 hours, change every 250 hours/ 12 months

CLUTCH FOR TURBOCOMPRESSOR
Capacity: 13 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

DIFFERENTIAL FRONT
Capacity: 8,5 liter

USE Normal		CLIMATE Moderate
----------------------	--	----------------------------

PRODUCT RECOMMENDATION 1 Gearlube LS 80W-90		
--	--	--

Check every 50 hours, change every 1000 hours/ 12 months

HUB REDUCTIONS FRONT
Capacity: 1,9 liter (each hub)

USE Normal		CLIMATE Moderate
----------------------	--	----------------------------

PRODUCT RECOMMENDATION 1 Gearlube LS 80W-90		
--	--	--

Check every 50 hours, change every 1000 hours/ 12 months

HUB REDUCTIONS REAR
Capacity: 12 liter (each hub)

USE Normal		CLIMATE Moderate
----------------------	--	----------------------------

PRODUCT RECOMMENDATION 1 Gearlube LS 80W-90		
--	--	--

Check every 50 hours, change every 1000 hours/ 12 months

SAME DIAMOND DIAMOND 270 DCR -> WSXL910200LS10001 (2008 AND AFTER)



POWER TAKE OFF FRONT

Capacity: 1,85 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	

Check every 250 hours, change every 500 hours

TRANSAXLE/TRANSMISSION

Capacity: 79 liter (Rigid rear axle), Capacity: 81 liter (Suspended rear axle)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	

Check every 50 hours, change every 1000 hours/ 12 months

AUXILIARY HYDRAULIC SYSTEM

Capacity: 45-75 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	

Check every 50 hours, change every 1000 hours/ 12 months

HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2032		

Change every 24 months

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 50 hours

SAME DIAMOND DIAMOND 270 DCR -> WSXL910200LS10001 (2008 AND AFTER)

**COOLING SYSTEM**

Capacity: 36 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Coolant SP 12 EVO***Check every 10 hours, change every 1000 hours/ 12 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.