

SAME DORADO DORADO 76 (2004-2006)

ENGINE Perkins 1000.4-W
Capacity: 12 liter, Filter capacity: 1 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Agridiesel MSP 15W-40

PRODUCT RECOMMENDATION 2
Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 3
Multifleet SHPD 15W-40

Check every 10 hours, change every 300 hours/ 12 months

USE
Initial service

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Agridiesel MSP 15W-40

PRODUCT RECOMMENDATION 2
Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 3
Multifleet SHPD 15W-40

Change every 50 hours

DIFFERENTIAL FRONT (4x4)
Capacity: 6 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Kroontrak MTH 10W-30

Check every 10 hours, change every 1200 hours/ 12 months

HUB REDUCTIONS FRONT (4x4)
Capacity: 1,5 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Kroontrak MTH 10W-30

Check every 10 hours, change every 1200 hours/ 12 months

TRANSAXLE/HYDRAULIC SYSTEM/POWER STEERING
Capacity: 41 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Agrifluid HT

Check every 10 hours, change every 1200 hours/ 12 months

SAME DORADO DORADO 76 (2004-2006)**HYDRAULIC BRAKE/CLUTCH SYSTEM**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

Change every 24 months

GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

Change every 50 hours

COOLING SYSTEM

Capacity: 11 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant -38 Organic NF		

Check every 10 hours, change every 1200 hours/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.