SAME FRUTTETO 3 FRUTTETO 3 S 80 - >1001 (2010 AND AFTER)



ENGINE 1000.3-WTI Euro 3 Capacity: 8 liter, Filter capacity: 1 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Agrisynth LSP 10W-40	Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	
Check every 10 hours, change every 300 hours/ 12 months			
USE		CLIMATE	
Biodiesel B100		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Agrisynth LSP 10W-40	Agridiesel MSP 15W-40	Agridiesel CRD+ 15W-40	

DIFFERENTIAL FRONT Capacity: 6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	
	·	· · · · · · · · · · · · · · · · · · ·

Check every 300 hours, change every 1200 hours/ 12 months

Check every 10 hours, change every 150 hours

HUB REDUCTIONS FRONT Capacity: 1,5 liter (each hub)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	
Check every 300 hours, change ev	rery 1200 hours/ 12 months	

TRANSAXLE/HYDRAULIC SYSTE Capacity: 41 liter	EM	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Agrifluid HT-Plus	Agrifluid HT	
Check every 50 hours, change eve	ry 1200 hours/ 12 months	

SAME FRUTTETO 3 FRUTTETO 3 S 80 ->1001 (2010 AND AFTER)



HYDRAULIC BRAKE/CLUTCH SYSTEM		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
SP Matic 2032		
Check every 50 hours, change every 24 months		

GREASE POINTS/NIPPLES			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2	
Change every 50 hours	1	1	

COOLING SYSTEM Capacity: 12 liter	
use Normal	climate Moderate
PRODUCT RECOMMENDATION 1 Coolant SP 12 EVO	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Check every 10 hours, change every 1200 hours/ 12 months