PRODUCT RECOMMENDATION

SAME RUBIN RUBIN 120 (1999 AND AFTER)



| ENGINE 1000.6-WT Capacity: 15,5 liter, Filter capacity: 0,5 liter | | |
|--|--|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SHPD 15W-40 | | |
| Check every 10 hours, change every 300 hours/ 12 months | | |
| USE | | CLIMATE |
| First change only | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Multifleet SHPD 15W-40 | | |
| Change every 50 hours | | |

| DIFFERENTIAL FRONT (4x4) Capacity: 13 liter | | |
|---|--|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Agrifluid HT | | |
| Check every 150 hours, change every 1200 hours/ 12 months | | |

| HUB REDUCTIONS FRONT (4x4) Capacity: 2,5 liter | |
|---|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Agrifluid HT | |
| | |

Check every 150 hours, change every 1200 hours/ 12 months

| POWER TAKE OFF FRONT Capacity: 2,5 liter | | |
|---|--|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Agrifluid HT | | |
| Check every 150 hours, change every 1200 hours/ 12 months | | |



| TRANSAXLE/HYDRAULIC SYSTEM/POWER STEERING 27/27 Capacity: 108 liter | | |
|--|--|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Agrifluid HT | | |
| | | |

Check every 150 hours, change every 1200 hours/ 12 months

| HYDRAULIC BRAKE/CLUTCH SYSTEM Capacity: 0,8 liter | |
|--|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| ATF Dexron II-D | |
| | |

Check every 300 hours, change every 24 months

| GREASE POINTS/NIPPLES | | |
|--------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |

Check every 50 hours

| COOLING SYSTEM Capacity: 16 liter | | |
|--------------------------------------|----------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Coolant -33 MPG | | |
| Check every 10 hours, change every 2 | 4 months | |

| AIRCONDITIONING | COMPRESSOR |
|---------------------|------------|
| Capacity: 1,8 liter | |

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.