## SAME SOLARIS SOLARIS 25 (2000 AND AFTER)



ENGINE K3F-D Capacity: 4 liter, Filter capacity: 0,4 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SHPD 15W-40		
Check every 10 hours, change every 300 h	nours/ 12 months	
USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SHPD 15W-40		

Change every 50 hours

<b>DIFFERENTIAL FRONT</b> Capacity: 4,8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 300 hours, change every 2400 hours/ 12 months

TRANSAXLE/HYDRAULIC SYSTEM Capacity: 21 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Kroontrak MTH 10W-30	
	· ·

Check every 300 hours, change every 1200 hours/ 12 months

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Ohaali aan E0 haam		·

Check every 50 hours

## SAME SOLARIS SOLARIS 25 (2000 AND AFTER)



COOLING SYSTEM Capacity: 4,5 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Coolant -38 Organic NF	Coolant -26			

Check every 10 hours, change every 1200 hours/24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.