

# SAME TIGER TIGER 50 E - >S10S453WT1E1001 (2008 AND AFTER)

**ENGINE 1000.3-WT3E1**

Capacity: 7,7 liter, Filter capacity: 1 liter

| USE                          |                               | CLIMATE                       |
|------------------------------|-------------------------------|-------------------------------|
| Normal                       |                               | Moderate                      |
| PRODUCT RECOMMENDATION 1     | PRODUCT RECOMMENDATION 2      | PRODUCT RECOMMENDATION 3      |
| <b>Agridiesel MSP 15W-40</b> | <b>Agridiesel CRD+ 15W-40</b> | <b>Multifleet SHPD 15W-40</b> |

Check every 10 hours, change every 300 hours/ 12 months

**DIFFERENTIAL FRONT**

Capacity: 6 liter

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>Agrifluid HT-Plus</b> | <b>Agrifluid HT</b>      |          |

Check every 300 hours, change every 1200 hours/ 12 months

**HUB REDUCTIONS FRONT**

Capacity: 1,5 liter (each hub)

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>Agrifluid HT-Plus</b> | <b>Agrifluid HT</b>      |          |

Check every 300 hours, change every 1200 hours/ 12 months

**TRANSAXLE/HYDRAULIC SYSTEM**

Capacity: 35 liter

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>Agrifluid HT-Plus</b> | <b>Agrifluid HT</b>      |          |

Check every 50 hours, change every 1200 hours/ 12 months

**HYDRAULIC BRAKE SYSTEM**

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>SP Matic 2032</b>     |  |          |

Check every 10 hours, change every 24 months

# SAME TIGER TIGER 50 E -

## >S10S453WT1E1001 (2008 AND AFTER)



### GREASE POINTS/NIPPLES

| USE                      |                                 | CLIMATE                      |
|--------------------------|---------------------------------|------------------------------|
| Normal                   |                                 | Moderate                     |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

*Change every 50 hours*

### COOLING SYSTEM

Capacity: 11 liter

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Coolant SP 12 EVO</b> |  |          |

*Check every 10 hours, change every 1200 hours/ 12 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*