

SAMPO ROSENLEW 2000 SERIES SR2085TS

ENGINE Sisu
Capacity: 26 liter

USE
Normal

CLIMATE
Mediterranean

PRODUCT RECOMMENDATION 1
Agridiesel CRD+ 15W-40

PRODUCT RECOMMENDATION 2
Multifleet SHPD 10W-40

PRODUCT RECOMMENDATION 3
Multifleet SHPD 15W-40

Check every 10 hours, change every 300 hours/ 12 months

FINAL DRIVES CIT
Capacity: 3 liter (each side)

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2
Unigear HS GL-3/GL-5 80W-90

PRODUCT RECOMMENDATION 3
Gearlube GL-5 85W-140

Change every 1200 hours/ 24 months

FINAL DRIVES Dana
Capacity: 6 liter (Left), Capacity: 5,5 liter (Right)

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2
Unigear HS GL-3/GL-5 80W-90

PRODUCT RECOMMENDATION 3
Gearlube GL-5 85W-140

Change every 1200 hours/ 24 months

GEARBOX HYDROSTATIC
Capacity: 3,5 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2
Unigear HS GL-3/GL-5 80W-90

PRODUCT RECOMMENDATION 3
Gearlube GL-5 85W-140

Change every 600 hours/ 12 months

GEARBOX MECHANICAL
Capacity: 3 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1
Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2
Unigear HS GL-3/GL-5 80W-90

PRODUCT RECOMMENDATION 3
Gearlube GL-5 85W-140

Change every 600 hours/ 12 months

SAMPO ROSENLEW 2000 SERIES SR2085TS**GRAIN ELEVATOR GEARBOX**

Capacity: 0,25 kg

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gear Grease EP 00/000*Change every 50 hours***KNIFE DRIVE GEARBOX**

Capacity: 0,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90

PRODUCT RECOMMENDATION 3

Gearlube GL-5 85W-140*Change every 600 hours/ 12 months***RETURN AUGER GEARBOX**

Capacity: 0,35 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90

PRODUCT RECOMMENDATION 3

Gearlube GL-5 85W-140*Change every 600 hours/ 12 months***HYDRAULIC SYSTEM**

Capacity: 14 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Perlus H 46*Change every 600 hours/ 12 months***GREASE POINTS/NIPPLES GREASE LUBRICATED**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Labora Grease

PRODUCT RECOMMENDATION 2

Q5 MP Calcep Grease EP 2

PRODUCT RECOMMENDATION 3

MP Lithep Grease EP 2*Change every 50 hours*

SAMPO ROSENLEW 2000 SERIES SR2085TS**GREASE POINTS/NIPPLES OIL LUBRICATED**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Kroontrak MTH 10W-30		

Change every 50 hours

COOLING SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Change every 1200 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.