SHIBAURA S SERIES S 435 SSS (2000 AND AFTER)



| ENGINE N844 Capacity: 6 liter | | |
|----------------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agridiesel MSP 15W-40 | Agridiesel CRD+ 15W-40 | Kroontrak MTH 10W-30 |

Check every 10 hours, change every 100 hours

| DIFFERENTIAL FRONT Capacity: 5 liter | | |
|---|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrifluid HT-Plus | Kroontrak MTH 10W-30 | Agrifluid HT |
| Chook overy 50 hours, change eve | 200 hours | <u>'</u> |

Check every 50 hours, change every 300 hours

| TRANSAXLE/HYDRAULIC SYSTE Capacity: 29 liter | EM | |
|--|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Agrifluid HT-Plus | Kroontrak MTH 10W-30 | Agrifluid HT |
| 01 1 501 | 0001 | |

Check every 50 hours, change every 300 hours

| HYDRAULIC SYSTEM POWER STEERING Capacity: 1,8 liter | | |
|---|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Perlus Biosynth 32 | Perlus H 32 | Perlus AF 32 |
| Charle avant 50 hours, shanga ava | ry 600 hours | |

Check every 50 hours, change every 600 hours

| GREASE POINTS/NIPPLES | | |
|--------------------------|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 |
| Check every 50 hours | · | |

SHIBAURA S SERIES S 435 SSS (2000 AND AFTER)



| COOLING SYSTEM Capacity: 6,2 liter | | |
|------------------------------------|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant -38 Organic NF | Coolant -26 | |
| Check every 10 hours, change every | / 12 months | · |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.