## **STEYR 9000 M9094A TURBO** (1994-2000)



ENGINE WD 401.81 Capacity: 8,5 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SHPD 15W-40	Multifleet SHPD 20W-50	Multifleet SCD 40
Check every 10 hours, change every 250	hours/ 12 months	·
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak MTH 10W-30	Multifleet SHPD 10W-40	Multifleet SCD 20W-20
Check every 10 hours, change every 250	hours/ 12 months	·
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		

DIFFERENTIAL FRONT LIMITED SLI Capacity: 5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Charles are 12 man that 500 have a	4000   404   4

Check every 12 months/ 500 hours, change every 1000 hours/ 24 months

Check every 10 hours, change every 250 hours/ 12 months

HUB REDUCTIONS FRONT (4x4) Capacity: 0,7 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube LS 80W-90	
Check every 12 months/ 500 hours, change every	y 1000 hours/ 24 months

## **STEYR 9000 M9094A TURBO** (1994-2000)



TRANSAXLE MANUAL 32/32 Capacity: 34 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid HT-Plus	Kroontrak MTH 10W-30	Agrifluid HT
Charles averaged 42 magnifical E00 hours	abanas avam (4000 bavas / 2.4 maantha	<u>'</u>

Check every 12 months/ 500 hours, change every 1000 hours/ 24 months

HYDRAULIC SYSTEM POWER ST Capacity: 30 liter	<b>FEERING</b>	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
ATF Dexron II-D	Perlus H 46	Perlus AF 46
	<u> </u>	

Check every 12 months/ 500 hours, change every 1000 hours/ 24 months

HYDRAULIC BRAKE SYSTEM Capacity: 0,4 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
LHM +	

Check every 12 months/ 500 hours, change every 1000 hours/ 24 months

GREASE POINTS/NIPPLES OTHERS		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
	<u>'</u>	

Check every 50 hours

GREASE POINTS/NIPPLES WHEEL BEARINGS		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Labora Grease	Multi Purpose Grease 3	
Check every 50 hours		•

## **STEYR 9000 M9094A TURBO** (1994-2000)



COOLING SYSTEM Capacity: 12 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Change every 1000 hours/24 month	78	-

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.