PRODUCT RECOMMENDATION

STEYR 80 SERIES (8100-8180) 8165A TURBO (COMBINED TRANSAXLE/HYDRAULICS) (1987-1995)

ENGINE WD 612.86-HPCE
Capacity: 14 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SHPD 15W-40	**Multifleet SHPD 20W-50**	**Multifleet SCD 30**

Check every 10 hours, change every 250 hours/ 12 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Kroontrak MTH 10W-30	**Multifleet SHPD 10W-40**	

Check every 10 hours, change every 250 hours/ 12 months

USE		CLIMATE
First change only		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Multifleet SHPD 15W-40	**Multifleet SHPD 20W-50**	**Multifleet SCD 30**

Change every 30 hours

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Kroontrak MTH 10W-30	**Multifleet SHPD 10W-40**	

Change every 30 hours

DIFFERENTIAL FRONT LTA D 218
Capacity: 9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Check every 12 months/ 500 hours, change every 1000 hours/ 24 months

DIFFERENTIAL FRONT Steyr VA
Capacity: 15 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Check every 12 months/ 500 hours, change every 1000 hours/ 24 months

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

STEYR 80 SERIES (8100-8180) 8165A TURBO (COMBINED TRANSAXLE/HYDRAULICS) (1987-1995)

HUB REDUCTIONS FRONT LTA D 218
Capacity: 1,75 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Check every 12 months/ 500 hours, change every 1000 hours/ 24 months

HUB REDUCTIONS FRONT Steyr VA
Capacity: 1,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Check every 12 months/ 500 hours, change every 1000 hours/ 24 months

TRANSAXLE/HYDRAULIC SYSTEM
Capacity: 85 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Kroontrak CVT 10W-40	**Kroontrak MTH 10W-30**	

Check every 12 months/ 500 hours, change every 1000 hours/ 24 months

HYDRAULIC BRAKE SYSTEM
Capacity: 0,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid DOT 5.1	**Drauliquid-LV Super DOT 4**	**Drauliquid-S DOT 4**

Check every 10 hours, change every 2000 hours/ 24 months

POWER STEERING
Capacity: 2,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

Check every 12 months/ 500 hours, change every 1000 hours/ 24 months

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

STEYR 80 SERIES (8100-8180) 8165A TURBO (COMBINED TRANSAXLE/HYDRAULICS) (1987-1995)

GREASE POINTS/NIPPLES OTHERS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	**Q5 MP Calcep Grease EP 2**	**MP Lithep Grease EP 2**

Check every 50 hours

GREASE POINTS/NIPPLES WHEEL BEARINGS

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Labora Grease	**Multi Purpose Grease 3**	

Check every 500 hours

COOLING SYSTEM
Capacity: 27 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	**Coolant -26**	

Check every 10 hours, change every 1000 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367