PRODUCT RECOMMENDATION

TORO UTILITY VEHICLES WORKMAN HDX-D 4X4 07371TC, 310000001->

ENGINE Kubota 902D
Capacity: 3,3 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		

Check every 10 hours, change every 150 hours

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	**Kroontrak MTH 10W-30**	**Multifleet SHPD 10W-40**

Check every 10 hours, change every 150 hours

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Asyntho 5W-30	**Armado Synth 5W-30**	

Check every 10 hours, change every 150 hours

USE		CLIMATE
First change only		Mediterranean
PRODUCT RECOMMENDATION 1		
Multifleet SCD 30		

Check every 10 hours, change every 50 hours

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Kroontrak CVT 10W-40	**Kroontrak MTH 10W-30**	**Multifleet SHPD 10W-40**

Check every 10 hours, change every 50 hours

USE		CLIMATE
First change only		Cold
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Asyntho 5W-30	**Armado Synth 5W-30**	

Check every 10 hours, change every 50 hours

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

TORO UTILITY VEHICLES WORKMAN HDX-D 4X4 07371TC, 310000001->

DIFFERENTIAL FRONT

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Agrifluid Synth XHP Ultra	**Agrifluid HT-Plus**	**Kroontrak MTH 10W-30**

Check every 1 months/ 100 hours, change every 800 hours

TRANSAXLE AUTOMATIC
Capacity: 7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	**ATF Almirol**	

Check every 10 hours, change every 800 hours

HYDRAULIC SYSTEM
Capacity: 15 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Perlus H 46		

Check every 10 hours, change every 800 hours

HYDRAULIC BRAKE SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

Check every 10 hours, change every 1000 hours/ 24 months

COOLING SYSTEM
Capacity: 3,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	**Coolant -26**	

Check every 10 hours, change every 1000 hours/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367