

PRODUCT RECOMMENDATION

UNIMOG (MB) 427 U 1200, U 1250, U 1250 L (427) (1988-2001)



ENGINE Mercedes-Benz OM366A
Capacity: 14,5 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

Multifleet SCD 40

Check every 200 hours, change every 400 hours

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Multifleet SCD 30

Check every 200 hours, change every 400 hours

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agrisynth LSP 10W-40

PRODUCT RECOMMENDATION 2

Kroontrak CVT 10W-40

PRODUCT RECOMMENDATION 3

Agridiesel CRD+ 15W-40

Check every 200 hours, change every 400 hours

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Multifleet SCD 10W

Check every 200 hours, change every 400 hours

DIFFERENTIAL LOCK AIR OPERATED

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

HDX 20W-20

Check every 12 months/ 1600 hours

DIFFERENTIAL FRONT

Capacity: 2,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90

Check every 100 hours, change every 1600 hours/ 12 months

PRODUCT RECOMMENDATION

UNIMOG (MB) 427 U 1200, U 1250, U 1250 L (427) (1988-2001)



DIFFERENTIAL REAR

Capacity: 2,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 100 hours, change every 1600 hours/ 12 months

HUB REDUCTIONS FRONT

Capacity: 0,25 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 100 hours, change every 1600 hours/ 12 months

HUB REDUCTIONS REAR

Capacity: 0,25 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90	

Check every 100 hours, change every 1600 hours/ 12 months

POWER TAKE OFF

Capacity: 8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Multifleet SCD 10W		

Check every 800 hours, change every 1600 hours/ 12 months

PRODUCT RECOMMENDATION

UNIMOG (MB) 427 U 1200, U 1250, U 1250 L (427) (1988-2001)



POWER TAKE OFF HOUSING

Capacity: 1,4 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

Gearlube GL-4 80W-90

Check every 800 hours, change every 1600 hours/ 12 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-4 80W

Check every 800 hours, change every 1600 hours/ 12 months

TRANSMISSION MANUAL/P.T.O. 8/8

Capacity: 12 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

Gearlube GL-4 80W-90

Check every 800 hours, change every 1600 hours/ 12 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-4 80W

Check every 800 hours, change every 1600 hours/ 12 months

UNIMOG (MB) 427 U 1200, U 1250, U 1250 L (427) (1988-2001)



HYDRAULIC SYSTEM

Capacity: 31 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

Multifleet SCD 30*Change every 2400 hours/ 24 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Multifleet SCD 10W*Change every 2400 hours/ 24 months*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Perlus H 15*Change every 2400 hours/ 24 months*

HYDRAULIC SYSTEM DIFFERENTIAL LOCK

Capacity: 0,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

HDX 10W

PRODUCT RECOMMENDATION 2

ATF-A*Change every 1600 hours/ 12 months*

HYDROSTATIC DRIVE

Capacity: 11 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Multifleet SCD 10W

PRODUCT RECOMMENDATION 2

Perlus H 15*Check every 600 hours, change every 1200 hours/ 12 months*

UNIMOG (MB) 427 U 1200, U 1250, U 1250 L (427) (1988-2001)



FLUID CLUTCH

Capacity: 17,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Multifleet SCD 10W	Perlus H 15	

Check every 600 hours

HYDRAULIC BRAKE SYSTEM

Capacity: 0,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Drauliquid-S DOT 4		

Change every 12 months

HYDRAULIC CLUTCH SYSTEM

Capacity: 0,2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Drauliquid-S DOT 4		

Change every 12 months

UNIMOG (MB) 427 U 1200, U 1250, U 1250 L (427) (1988-2001)



POWER STEERING

Capacity: 2,25 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1 Multifleet SCD 30		
--	--	--

Change every 2400 hours/ 24 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1 Multifleet SCD 10W		
---	--	--

Change every 2400 hours/ 24 months

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1 ATF-A		
--	--	--

Change every 2400 hours/ 24 months

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1 Q5 MP Calcep Grease EP 2	PRODUCT RECOMMENDATION 2 MP Lithep Grease EP 2	
---	--	--

Check every 100 hours, change every 800 hours

COOLING SYSTEM

Capacity: 18 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1 Coolant SP 11		
--	--	--

Change every 36 months

UNIMOG (MB) 427 U 1200, U 1250, U 1250 L (427) (1988-2001)

**AIR COMPRESSOR**

Capacity: 0,1 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

Multifleet SCD 40*Change every 200 hours*

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Multifleet SCD 30*Change every 200 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Agrisynth LSP 10W-40

PRODUCT RECOMMENDATION 2

Kroontrak CVT 10W-40

PRODUCT RECOMMENDATION 3

Agridiesel CRD+ 15W-40*Change every 200 hours*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Multifleet SCD 10W*Change every 200 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.